

BFLDID(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
BFLDID Bfldid (char *fldnm);
```

```
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Get field id by field name passed in *fldnm* parameter. Note that field must be defined in field tables (**fd** files) (see `ex_env(5)`, variables **FIELDTBLS**, **FLDTBLDIR**).

Chapter 3

RETURN VALUE

On success, **Bfldid()** returns compiled file id; on error, **BBADFLDID** is returned.

Chapter 4

ERRORS

No errors are returned by this function.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Bfname(3)

Chapter 8

COPYING

© Mavimax, Ltd