

BBOOLCO(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
char * Bboolco (char *expr);
```

```
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Compile boolean expression (in parameter *expr*) and returns the evaluation tree handler. Following operators are available for expressions:

%%, *!%* - regular expression testing e.g. "T_STRING_2_FLD *%%* 58.*"- will match if T_STRING_2_FLD is set to "58ABC" for example.

==, *!=*, *<*, *<=*, *>*, *>=* - compare operations

!, *~*, *^* - bitwise operations

+, *-*, ***, *%*, */* - mathematical operations

&&, *||* - logical operations

Chapter 3

RETURN VALUE

On success, **Bboolco()** return pointer to evaluation tree; on error, NULL is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted.

BBADFLD Invalid field id passed.

BNOTPRES Field not present.

FMALLOC Malloc failed.

BSYNTAX Synax error in script.

BBADNAME Bad field name specified.

Chapter 5

EXAMPLE

See `ubftest/test_expr.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Bboolev(3) **Bfloatev(3)** **Btreefree(3)**

Chapter 8

COPYING

© Mavimax, Ltd