

TPGETLEV(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
int tpgetlev (void);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Function returns current status of global transaction. If transaction is started by **tpbegin()** or called service is part of global transaction (invoked by process in global TX and was not specified **TPNOTRAN**), then function returns *1*. If process is not part of global transaction, then return value is **0**.

Chapter 3

RETURN VALUE

0 - current thread is not part of global transaction. **1** - current thread is part of global transaction.

Chapter 4

ERRORS

Function does not return any errors.

Chapter 5

EXAMPLE

See `atmitest/test021_xafull/atmisv21.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

`tpcommit(3)` `tgetlev(3)` `tpopen(3)` `tpsuspend(3)` `tpresume(3)`

Chapter 8

COPYING

© Mavimax, Ltd