

**BDELETE(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1</a>	<a href="#">SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3</a>	<a href="#">RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4</a>	<a href="#">ERRORS</a>	<a href="#">4</a>
<a href="#">5</a>	<a href="#">EXAMPLE</a>	<a href="#">5</a>
<a href="#">6</a>	<a href="#">BUGS</a>	<a href="#">6</a>
<a href="#">7</a>	<a href="#">SEE ALSO</a>	<a href="#">7</a>
<a href="#">8</a>	<a href="#">COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
int Bdelete (UBFH *p_ub, BFLDID *fldlist);
```

Link with *-lubf -lnstd -lm -lpthread*

## Chapter 2

# DESCRIPTION

This function removes any field from *p\_ub* buffer which are present in *fdlist* array. The array must be terminated with **BBAD-FLDID**.

## Chapter 3

# RETURN VALUE

On success, **Bdelete()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_bproj.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

# Chapter 7

# SEE ALSO

**Bproj(3)** **Bprojcpx(3)**

# Chapter 8

# COPYING

© Mavimax, Ltd