

NDRXDEBUG.CONF(5)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	DEBUG CONFIGURATION FILE SYNTAX	3
4	EXAMPLE	4
5	BUGS	5
6	SEE ALSO	6
7	AUTHOR	7
8	COPYING	8

Chapter 1

SYNOPSIS

BINARY_NAME [ndrx=NDRX_DEBUG_LEVEL] [ubf=UBF_DEBUG_LEVEL] [tp=TP_DEBUG_LEVEL] [bufsz=DEBUG_BUFFER_SIZE] [threaded=THREADED] file=[LOG_FILE]

Chapter 2

DESCRIPTION

debug.conf a file specified by *NDRX_DEBUG_CONF* env variable configures EnduroX platform logging for each of the separate executable. The logging is done from two sources. One source is UBF and another is ATMI (ndrx). For each of the sources debug level can be set for each separate binary. Debug file or stderr also can be specified for each of the separate binaries.

Chapter 3

DEBUG CONFIGURATION FILE SYNTAX

BINARY_NAME

Binary name is either executable name or *. In case of * it is applied to default configuration. It is recommended to put it in start of the file. Any binary afterwards in file will override defaults.

NDRX_DEBUG_LEVEL

ATMI debug level. 0..5. 0=No logging, 1=Fatal, 2=Error, 3=Warning, 4=Program info, 5=Program detail.

UBF_DEBUG_LEVEL

UBF debug level. 0..5. 0=No logging, 1=Fatal, 2=Error, 3=Warning, 4=Program info, 5=Program detail.

TP_DEBUG_LEVEL

This is tplog(3) user logging level. 0..5. 0=No logging, 1=Fatal, 2=Error, 3=Warning, 4=Program info, 5=Program detail.

DEBUG_BUFFER_SIZE

Number of lines to buffer before writing out to disk.

THREADED

Value is can be set to "Y" or "N". The default is "N". In case of "N" then logging of the process debug output is sent to the *LOG_FILE*. All threads are doing logging to single file. If set to "Y", then for each XATMI client there will be open new log file. The log file names are assigned by following approach: Say *LOG_FILE* = **TEST.LOG**, then new thread log will go to **TEST.X.LOG** (.e.g **TEST.1.LOG**). If *LOG_FILE* = **TEST.LOG**, then new thread will perform logging to "TEST_LOG.1".

LOG_FILE

Log file. If empty then *stderr* will be used.

COMMENTS

Commented lines starts with #. Empty lines are ignored.

Chapter 4

EXAMPLE

Sample configuration:

```
# Global config:
* ndrxd=5 ubf=1 lines=1 bufisz=1000 tp=5 file=
# Per binary config:
xadmin      file=${NDRX_APPHOME}/tmp/XADMIN
ndrxd       file=${NDRX_APPHOME}/tmp/NDRXD
myclient    file=${NDRX_APPHOME}/tmp/MYCLIENT
myserver    file=${NDRX_APPHOME}/tmp/MYSERVER threaded=y
ud          file=${NDRX_APPHOME}/tmp/NDRX
```

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

`xadmin(8)`, `ndrxd(8)`, `ndrxconfig.xml(5)`

Chapter 7

AUTHOR

Enduro/X is created by Madars Vitolins.

Chapter 8

COPYING

© Mavimax, Ltd