

# TPISAUTOBUF(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1 SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2 DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3 RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4 ERRORS</a>	<a href="#">4</a>
<a href="#">5 BUGS</a>	<a href="#">5</a>
<a href="#">6 SEE ALSO</a>	<a href="#">6</a>
<a href="#">7 COPYING</a>	<a href="#">7</a>

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
int tpisautobuf (char *buf);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

## Chapter 2

# DESCRIPTION

Test the buffer for marking of *automatically allocated* by Enduro/X. Such buffers are made at point when they are passed to XATMI service routine by Enduro/X XATMI sub-system. In case if buffer is automatically allocated, return value will be **1**, in case if allocated by user's **tpalloc(3)** function will return **0**. In case of failure **-1** is returned. Function can be called by XATMI client, normally client processes allocates buffers are manually, but there could be one exception when multi-threaded XATMI server's main thread passed service call *object* to it's companion XATMI client thread by using **tpsrvgetctxdata(3)** and **tpsrvsetctxdata(3)**. In that case client process can get auto-buffer.

---

## Chapter 3

# RETURN VALUE

If buffer is auto-allocated, **tpisautobuf()** return 1; If manually by **tpalloc(3)** 0 is returned; in case of error, -1 is returned, with **tperrno** set to indicate the error.

## Chapter 4

# ERRORS

Note that **tpstrerror()** returns generic error message plus custom message with debug info from last function call.

**TPEINVAL** Invalid parameter is given to function. Either *buf* is NULL or *buf* not allocated by **tpalloc()**

---

## Chapter 5

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)



## Chapter 6

## SEE ALSO

**tpalloc(3) tpfree(3) tpsrvgetctxdata(3) tpsrvsetctxdata(3)**

# Chapter 7

# COPYING

© Mavimax, Ltd