

**TPREALLOC(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
char *tprealloc(char *ptr, long size);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

---

## Chapter 2

# DESCRIPTION

Reallocate (change the buffer size) of previously allocated resources by **tpalloc()**. The XATMI buffer is passed in with *ptr* parameters and new size is provided in *size* parameter. It is allowed to resize auto-allocated buffers (i.e. buffer that is passed into **TPSVCINFO.data** field.)

---

## Chapter 3

# RETURN VALUE

In case of success, function returns possibly new pointer of re-allocated memory. The pointer could be the same, for example if size is not changed of the buffer. In case of failure, function returns NULL and **tperrno** returns the error code.

## Chapter 4

# ERRORS

Note that **tpsterror()** returns generic error message plus custom message with debug info from last function call.

**TPEINVAL** Invalid *ptr* pointer passed in. Either buffer not allocated by **tpalloc()** or *ptr* is NULL.

**TPEOS** System failure occurred during serving. See logs i.e. user log, or debugs for more info.

---

## Chapter 5

# EXAMPLE

See `atmitest/test001_basiccall/atmiclt1.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

## Chapter 7

## SEE ALSO

**tpalloc(3) tpfree(3)**

## Chapter 8

# COPYING

© Mavimax, Ltd