

BVNULL(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
int Bvnull(char *cstruct, char *cname, BFLDOCC occ, char *view);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Test is field in structure *NULL*. The tests are done by comparing the field value with *NULL* value column defined in view file. Note that if *NULL* was set to **NONE**, then function will always return **FALSE**. The pointer to structure is given in *cstruct*. The field name is specified in *cname*. The array element index (zero based) is passed in *occ* field. If *COUNT* is set to 1 in view file, then field is tested via *occ* set to **0**.

Chapter 3

RETURN VALUE

If field is NULL, **Bvftos()** return **1**; If field is no NULL, function returns **0**; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BEINVAL Invalid value passed to function, parameters are NULL or invalid *occ* index.

BNOCNAME Invalid *cname* specified (field not found).

BBADVIEW View is not found, object file is defective or system error.

Chapter 5

EXAMPLE

See `atmitest/test040_typedview/viewunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

viewc(8) Bvstof(3) Bvftos(3) Bvsinit(3) Bvselinit(3) Bvnull(3) ex_env(5) Bupdate(3) Bconcat(3)

Chapter 8

COPYING

© Mavimax, Ltd