

# TPLOGCLOSEREQFILE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>ERRORS</b>	<b>4</b>
<b>5</b>	<b>EXAMPLE</b>	<b>5</b>
<b>6</b>	<b>BUGS</b>	<b>6</b>
<b>7</b>	<b>SEE ALSO</b>	<b>7</b>
<b>8</b>	<b>COPYING</b>	<b>8</b>

## Chapter 1

# SYNOPSIS

```
#include <ndebug.h>
```

```
void tplogclosereqfile(void);
```

Link with *-lnstd -lpthread -lrt -lm*

## Chapter 2

# DESCRIPTION

Close currently open request logging facility. It is not a problem to call a function twice. If request logger is closed nothing will happen. With this function logger will be degraded to thread logging facility (if was open) or to process based logging.

## Chapter 3

# RETURN VALUE

N/A

# Chapter 4

# ERRORS

N/A

## Chapter 5

# EXAMPLE

See `atmitest/test031_logging/atmict31.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

## Chapter 7

## SEE ALSO

[tplogclosethread\(3\)](#) [tplogsetreqfile\\_direct\(3\)](#) [tplogsetreqfile\(3\)](#) [tplogdump\(3\)](#) [tplogdumpdiff\(3\)](#) [tplog\(3\)](#) [tplogconfig\(3\)](#) [ex\\_devguid](#)

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd