

# TPSRVSETCTXDATA(3)

| REVISION HISTORY |      |             |      |
|------------------|------|-------------|------|
| NUMBER           | DATE | DESCRIPTION | NAME |
|                  |      |             |      |

# Contents

|          |                     |          |
|----------|---------------------|----------|
| <b>1</b> | <b>SYNOPSIS</b>     | <b>1</b> |
| <b>2</b> | <b>DESCRIPTION</b>  | <b>2</b> |
| <b>3</b> | <b>RETURN VALUE</b> | <b>3</b> |
| <b>4</b> | <b>ERRORS</b>       | <b>4</b> |
| <b>5</b> | <b>EXAMPLE</b>      | <b>5</b> |
| <b>6</b> | <b>BUGS</b>         | <b>6</b> |
| <b>7</b> | <b>SEE ALSO</b>     | <b>7</b> |
| <b>8</b> | <b>COPYING</b>      | <b>8</b> |

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
int tpsrvsetctxdata (char *data, long flags);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

## Chapter 2

# DESCRIPTION

Restore context data from previously saved (**tpsrvgetctxdata()**) context data. The *data* field is value returned by **tpsrvgetctxdata()**. This function is needed for multi threaded server, in order to restore tpcall() data in worker thread. If global transaction was running in main thread for which **tpsrvgetctxdata()** was called, then **tpsrvsetctxdata()** will resume the global transaction in current thread.

This function is available only for XATMI servers.

### Valid flags

**TPNOAUTBUF** Do not restore auto buffer when restoring the server context. This can be suitable in case if buffer is already made free by initial service thread and the target server/service does not know anything about given pointer. E.g. the context is copied to different process.

## Chapter 3

# RETURN VALUE

On success, **tpsrvsetctxdata()** return pointer to context data block; on error, NULL is returned, with **tperrno** set to indicate the error.

## Chapter 4

# ERRORS

Note that **tpstrerror()** returns generic error message plus custom message with debug info from last function call.

**TPEINVAL** *data* is NULL.

**TPEPROTO** Global transaction is already started.

**TPESYSTEM** System failure occurred during serving. See logs i.e. user log, or debugs for more info. Could be the case if XA sub-system is not open by **tpopen()**.

**TPEOS** System failure occurred during serving. See logs i.e. user log, or debugs for more info.

---

## Chapter 5

# EXAMPLE

See `atmitest/test017_srvthread/atmisv17.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

## Chapter 7

## SEE ALSO

**tpsrvgetctxdata(3) tpcontinue(3) tpinit(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd