

BMKFLDID(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

`#include <ubf.h>`

`BFLDID Bmkfldid (int fldtype, BFLDID bfldid);`

Link with `-lubf -lnstd -lm -lpthread`

Chapter 2

DESCRIPTION

Compile the field id by given type in *fldtype* and field id (not compiled) in *bfldid*. The compiled field id consists of type (moved to oldest 3 bits) and binary *ored* field id.

Chapter 3

RETURN VALUE

On success, **Bmkfldid()** return compiled filed id; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

No errors returned by this function.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Bfname(3)

Chapter 8

COPYING

© Mavimax, Ltd