

**TPFREECTXT(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1 SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2 DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3 RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4 ERRORS</a>	<a href="#">4</a>
<a href="#">5 EXAMPLE</a>	<a href="#">5</a>
<a href="#">6 BUGS</a>	<a href="#">6</a>
<a href="#">7 SEE ALSO</a>	<a href="#">7</a>
<a href="#">8 COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
void tpfreectxt(TPCONTEXT_T context);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

## Chapter 2

# DESCRIPTION

Function frees up the context data which was returned by **tpgetctxt(3)** function call. Function does not do the **tpterm(3)**. Thus to remove context data fully, firstly thread running with context must call **tpterm(3)**, then **tpgetctxt(3)** and then call **tpfreectxt()**.

This function uses underlying thread local storage infrastructure which is provided separately for each of the major Enduro/X libraries - libnstd (Standard library), libubf (UBF buffer library) and libatmi (ATMI library). If operations at library levels are required, then following functions can be used:

1. `ndrx_nstd_tls_new()`, `ndrx_ubf_tls_new()`, `ndrx_atmi_tls_new()` - allocate TLS data for library.
  2. `ndrx_nstd_tls_get()`, `ndrx_ubf_tls_get()`, `ndrx_atmi_tls_get()` - get the TLS data for library (currently associated with thread).
  3. `ndrx_nstd_tls_set()`, `ndrx_ubf_tls_set()`, `ndrx_atmi_tls_set()` - set the thread local data from saved pointer.
  4. `ndrx_nstd_tls_free()`, `ndrx_ubf_tls_free()`, `ndrx_atmi_tls_free()` - free the thread local data.
-

## Chapter 3

# RETURN VALUE

N/A

---

# Chapter 4

# ERRORS

N/A

## Chapter 5

# EXAMPLE

See `atmitest/test016_contextsw/atmict16.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

## Chapter 7

## SEE ALSO

**`tpgetctx(3)` `tpsetctx(3)` `tpsrvsetctxdata(3)` `tpsrvgetctxdata(3)` `tpcontinue(3)` `tpinit(3)`**

## Chapter 8

# COPYING

© Mavimax, Ltd