

BSIZEOF(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
long Bsizeof (UBFH *p_ub);
```

```
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Return the UBF buffer size in bytes.

Chapter 3

RETURN VALUE

On success, **Bsizeof()** return buffer size; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Bsterror(3) can give more description for error (for last call).

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted. p_ub is NULL.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Binit(3) Bused(3) Bunused(3)

Chapter 8

COPYING

© Mavimax, Ltd