

TPLOGCLOSEREQFILE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ndebug.h>
```

```
void tplogclosereqfile(void);
```

Link with *-lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Close currently open request logging facility. It is not a problem to call a function twice. If request logger is closed nothing will happen. With this function logger will be degraded to thread logging facility (if was open) or to process based logging.

Chapter 3

RETURN VALUE

N/A

Chapter 4

ERRORS

N/A

Chapter 5

EXAMPLE

See `atmitest/test031_logging/atmiclt31.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

[tplogclosethread\(3\)](#) [tplogsetreqfile_direct\(3\)](#) [tplogsetreqfile\(3\)](#) [tplogdump\(3\)](#) [tplogdumpdiff\(3\)](#) [tplog\(3\)](#) [tplogconfig\(3\)](#) [ex_devguid](#)

Chapter 8

COPYING

© Mavimax, Ltd