

TPEXT_DELB4POLLCB(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|-------------------|------------------------------|-------------------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
int tpext_delb4pollcb(void);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Function removes previously registered callback by **tpext_addb4pollcb()** function. It is not an error to call this function twice. This function is available only for XATMI servers.

Chapter 3

RETURN VALUE

On success, **tpext_delb4pollcb()** return zero; on error, -1 is returned, with **tperrno** set to indicate the error.

Chapter 4

ERRORS

At current version function always succeeds.

Chapter 5

EXAMPLE

See `atmitest/test008_extensions/atmisv.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

`tpext_addb4pollcb(3)`

Chapter 8

COPYING

© Mavimax, Ltd