

EDB_COPY(8)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	OPTIONS	3
4	EXIT STATUS	4
5	BUGS	5
6	AUTHOR	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

edb_copy [-V] [-c] [-n] **srcpath** [**dstpath**]

Chapter 2

DESCRIPTION

The **edb_copy** utility copies an EXDB environment. The environment can be copied regardless of whether it is currently in use. No lockfile is created, since it gets recreated at need.

If *dspath* is specified it must be the path of an empty directory for storing the backup. Otherwise, the backup will be written to stdout.

Chapter 3

OPTIONS

[-V]

Write the library version number to the standard output, and exit.

[-c]

Compact while copying. Only current data pages will be copied; freed or unused pages will be omitted from the copy. This option will slow down the backup process as it is more CPU-intensive. Currently it fails if the environment has suffered a page leak.

[-n]

Open LDMB environment(s) which do not use subdirectories.

Chapter 4

EXIT STATUS

Exit status is zero if no errors occur. Errors result in a non-zero exit status and a diagnostic message being written to standard error.

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

AUTHOR

Howard Chu of Symas Corporation <http://www.symas.com>

Chapter 7

SEE ALSO

`edb_stat(8)`

Chapter 8

COPYING

© Symas Corporation © Mavimax, Ltd