

# TPLOGSETREQFILE\_DIRECT(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1</a>	<a href="#">SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3</a>	<a href="#">RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4</a>	<a href="#">ERRORS</a>	<a href="#">4</a>
<a href="#">5</a>	<a href="#">BUGS</a>	<a href="#">5</a>
<a href="#">6</a>	<a href="#">SEE ALSO</a>	<a href="#">6</a>
<a href="#">7</a>	<a href="#">COPYING</a>	<a href="#">7</a>

## Chapter 1

# SYNOPSIS

```
#include <ndebug.h> #include <nerror.h>
void tplogsetreqfile_direct(char *filename);
Link with -lnstd -lpthread -lrt -lm
```

## Chapter 2

# DESCRIPTION

Function opens **LOG\_FACILITY\_TP\_REQUEST** facility for logging. The logging is performed to specified *filename* file. If it fails to set the log file, the logger will write the logs to **stderr**. No error is returned.

# Chapter 3

# RETURN VALUE

N/A

# Chapter 4

# ERRORS

N/A

## Chapter 5

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)



## Chapter 6

## SEE ALSO

**tplogdump(3)** **tplogdumpdiff(3)** **tplog(3)** **tplogsetreqfile\_direct(3)** **tplogsetreqfile(3)** **ex\_devguide(guides)** **ndrxdebug.conf(5)**

## **Chapter 7**

# **COPYING**

© Mavimax, Ltd