

TPGETNODEID(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1 SYNOPSIS	1
2 DESCRIPTION	2
3 RETURN VALUE	3
4 ERRORS	4
5 BUGS	5
6 SEE ALSO	6
7 COPYING	7

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
long tpgetnodeid(void);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Function returns current cluster node id. Basically that is configured in **NDRX_NODEID** environment variable, see **ex_env(5)** page.

Chapter 3

RETURN VALUE

On success, **tpgetnodeid()** return cluster node id (>0); on error, -1 is returned, with **tperrno** set to indicate the error.

Chapter 4

ERRORS

Note that **tpstrerror()** returns generic error message plus custom message with debug info from last function call.

TPESYSTEM System failure occurred during serving. See logs i.e. user log, or debugs for more info.

TPEOS System failure occurred during serving. See logs i.e. user log, or debugs for more info.

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

ex_env(5)

Chapter 7

COPYING

© Mavimax, Ltd