

BFLDDBUNLOAD(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	EXAMPLE	4
5	BUGS	5
6	SEE ALSO	6
7	COPYING	7

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
void Bflddbunload(void);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Function closes LMDB handlers which are open for custom field database. Function is not thread safe in respect to other Bflddb* functions.

If DB is already closed, then function will do nothing.

Currently Enduro/X at process exist does not unload the database handles. It is expected that OS will free any IPC (semaphores) automatically.

Chapter 3

RETURN VALUE

There is no return value.

Chapter 4

EXAMPLE

See `atmitest/test050_ubfdb/atmiclt50.c` for sample code.

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

Bflddbid(3) Bflddbname(3) Bflddbload(3) Bflddbunlink(3) Bflddbdrop(3) Bflddbdel(3) Bflddbadd(3) Bflddbget(3) ubfdb.ini(5)

Chapter 7

COPYING

© Mavimax, Ltd