

BSUBSET(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
int Bsubset (UBFH *p_ubf1, UBFH *p_ubf2);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Test that *p_ubf2* (needle) is found in *p_ubf1* (haystack).

Chapter 3

RETURN VALUE

If *p_ubf2* occurrences, fields and values are found in *p_ubf1* the function returns **1**, if there are any differences, function returns 0 (not found). In case of error -1 is returned with **Berror** set accordingly.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BEINVAL *p_ubf1* or *p_ubf2* are NULL pointers.

BNOTFLD *p_ubf1* or *p_ubf2* buffers not fielded, not correctly allocated or corrupted.

Chapter 5

EXAMPLE

See `ubftest/test_bcmp.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bcmp(3)

Chapter 8

COPYING

© Mavimax, Ltd