

**BERROR(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1 SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2 DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3 RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4 ERRORS</a>	<a href="#">4</a>
<a href="#">5 EXAMPLE</a>	<a href="#">5</a>
<a href="#">6 BUGS</a>	<a href="#">6</a>
<a href="#">7 SEE ALSO</a>	<a href="#">7</a>
<a href="#">8 COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
#define Berror (*_Bget_Ferror_addr())
```

Link with *-lubf -lnstd -lm -lpthread*

## Chapter 2

# DESCRIPTION

Return the error code of last UBF operation. To get the description of the error, use Bsterror(3) function.

## Chapter 3

# RETURN VALUE

Returns the last error code.

## Chapter 4

# ERRORS

**BMINVAL** No error.

**BALIGNERR** Unified buffer not UBF or corrupted.

**BNOTFLD** Unified buffer not UBF or corrupted.

**BNOSPACE** No space for adding new field to buffer.

**BNOTPRES** Field not present in buffer.

**BBADFLD** Bad field ID.

**BTYPERR** Invalid field type. Note that Field types are defined following: BFLD\_SHORT (matches C short), BFLD\_LONG (matches C long), BFLD\_CHAR (matches C char), BFLD\_FLOAT (matches C float), BFLD\_DOUBLE (matches C double), BFLD\_STRING (match C char\* - NUL terminated), BFLD\_CARRAY (matches C char\*)

**BEUNIX** Unix error.

**BBADNAME** Bad field name.

**BMALLOC** Failed to allocate memory.

**BSYNTAX** Boolean expressions syntax error.

**BFTOPEN** Failed to open field table.

**BFTSYNTAX** Invalid field table syntax.

**BEINVAL** Invalid argument passed to function.

---

## Chapter 5

# EXAMPLE

See `ubftest/ubfunit1.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

## Chapter 7

## SEE ALSO

**CBchg(3) Badd(3) Binit(3) Bstrerror(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd