

CBFIND(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
char * Bfinds (UBFH *p_ub, BFLDID bfldid, BFLDOCC occ);
```

```
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Function on success returns pointer to data field present in UBF buffer, converted to **BFLD_STRING**. *p_ub* is pointer to UBF buffer, *bfldid* is field id, *occ* is field occurrence at buffer, which needs to be found. Returned pointer is valid only until next UBF operation call, as the converted value is stored in thread local storage used for various UBF operations.

The function in practice invokes **CBfind(3)** with user type **BFLD_STRING** and len set to NULL.

Chapter 3

RETURN VALUE

On success, **Bfinds()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted.

BNOTPRES Field not present.

BMALLOC Failed to allocate type conversion buffer.

Chapter 5

EXAMPLE

See `ubftest/test_macro.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bchg(3) Badd(3) CBadd(3) Bfind(3) Bfindocc(3) Bfindlast(3)

Chapter 8

COPYING

© Mavimax, Ltd