

BGETSA(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
char * Bgetsa (UBFH *p_ub, BFLDID bflid, BFLDOCC occ, BFLDLEN *extralen);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Function is used to get field data from UBF buffer. *p_ub* is pointer to UBF buffer, *bflid* is field id, *occ* is field occurrence at buffer, which needs to be read. The value of the field is returned by this function. The pointer returned is memory block allocated by this function. Later this needs to be freed by `free()` system call. If *extralen* is not NULL, then on input it indicates number of extra bytes to allocate.

This is macro function and it invokes **CBgetalloc(3)** with field type **BFLD_STRING**.

Chapter 3

RETURN VALUE

On success, **Bgetsa()** return pointer to memory block with data; on error, NULL is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted.

BNOSPACE No space in *buf*.

BMALLOC Failed to allocate type conversion buffer.

BBADFLD Invalid field id passed.

BNOTPRES Field not present.

Chapter 5

EXAMPLE

See `ubftest/test_macro.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bchg(3) Badd(3) CBadd(3) Bget(3) CBget(3) CBgetalloc(3)

Chapter 8

COPYING

© Mavimax, Ltd