

**CBFIND(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * CBfind (UBFH *p_ub, BFLDID bfldid, BFLDOCC occ, BFLDLEN *len, int usrtype);
```

```
Link with -lubf -lnstd -lm -lpthread
```

---

## Chapter 2

# DESCRIPTION

Function on success returns pointer to data field present in UBF buffer, converted to user type specified in *usrtype*. *p\_ub* is pointer to UBF buffer, *bfdid* is field id, *occ* is field occurrence at buffer, which needs to be found. *len* is output paramter for indicating the type length in bytes. Then *len* is optional. Returned pointer is valid only until next UBF operation call, as the converted value is stored in thread local storage used for varous UBF operations.

## Chapter 3

# RETURN VALUE

On success, **CBfind()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

**BNOTPRES** Field not present.

**BMALLOC** Failed to allocate type conversion buffer.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_find.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bchg(3) Badd(3) CBadd(3) Bfind(3) CBfindocc(3) CBfindlast(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd