

BMKFLDID(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

`#include <ubf.h>`

`BFLDID Bmkfldid (int fldtype, BFLDID bfldid);`

Link with `-lubf -lnstd -lm -lpthread`

Chapter 2

DESCRIPTION

Compile the field id by given type in *fldtype* and field id (not compiled) in *bfldid*. The compiled field id consists of type (moved to oldest 3 bits) and binary *ored* field id.

Chapter 3

RETURN VALUE

On success, **Bmkfldid()** return compiled filed id; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

No errors returned by this function.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bfname(3)

Chapter 8

COPYING

© Mavimax, Ltd