

TPSRVFREECTXDATA(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
void tpsrvfreectxdata(char *p_buf);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Function is used for deallocating the server context data allocated either by **tpsrvgetctxdata(3)** or **tpsrvgetctxdata2()**.

This function is available only for XATMI servers.

Chapter 3

RETURN VALUE

Function does not return a value.

Chapter 4

ERRORS

Function does not return an error.

Chapter 5

EXAMPLE

See `atmitest/test017_srvthread/atmisv17.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

tpsetctxdata(3) tpsrvgetctxdata(3) tpcontinue(3) tpinit(3)

Chapter 8

COPYING

© Mavimax, Ltd