

**TPURCODE(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>BUGS</b>	<b>3</b>
<b>4</b>	<b>SEE ALSO</b>	<b>4</b>
<b>5</b>	<b>COPYING</b>	<b>5</b>

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
#define tpurcode (*_exget_tpurcode_addr())
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

---

## Chapter 2

# DESCRIPTION

Macro returns the *r*code value which is returned by XATMI server. The value is saved in global variable after **tpcall(3)** performed. The *r*code is available (i.e. reset to new value) only if server processes did generate the response. I.e. in case of **TPENOENT** error, the tpurcode() will return previous value.

## Chapter 3

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 4

## SEE ALSO

`tpreturn(3)` `tpcall(3)`

## **Chapter 5**

# **COPYING**

© Mavimax, Ltd