

**CBGETALLOC(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1 SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2 DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3 RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4 ERRORS</a>	<a href="#">4</a>
<a href="#">5 EXAMPLE</a>	<a href="#">5</a>
<a href="#">6 BUGS</a>	<a href="#">6</a>
<a href="#">7 SEE ALSO</a>	<a href="#">7</a>
<a href="#">8 COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * CBgetalloc (UBFH *p_ub, BFLDID bfldid, BFLDOCC occ, int usrtype, BFLDLEN *extralen);
```

```
Link with -lubf -lnstd -lm -lpthread
```

---

## Chapter 2

# DESCRIPTION

Get the field *bfl**did* at *occ* occurrence from *p\_ub* buffer. The value is converted to *usrtype*. The value is returned (copied to) to memory block allocated by function. There is extra parameter *extralen*. On input it indicates the additional space that shall be allocated. The *extralen* can be NULL, in that case no extra memory is allocated.

Function is based on **Bgetalloc(3)**, which does not convert to user type, but returns direct value.

## Chapter 3

# RETURN VALUE

On success, **CBgetalloc()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

**BNOTPRES** Field not present.

**BMALLOC** Failed to allocate type conversion buffer.

**BBADFLD** Invalid field passed to *bfldid*.

**BTYPERR** Invalid user type specified.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_get.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bchg(3) Badd(3) CBadd(3) Bfind(3) Bgetalloc(3)**

## Chapter 8

# COPYING

© Mavimax, Ltd