

**BERROR(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>EXAMPLE</b>	<b>4</b>
<b>5</b>	<b>BUGS</b>	<b>5</b>
<b>6</b>	<b>SEE ALSO</b>	<b>6</b>
<b>7</b>	<b>COPYING</b>	<b>7</b>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
void B_error (char *str);
```

Link with *-lubf -lnstd -lm -lpthread*

## Chapter 2

# DESCRIPTION

The principle is similar to **perror()** POSIX function call. Function prints the last UBF error message including user message (in *str*) to **stderr**.

## Chapter 3

# RETURN VALUE

Function is void and does not return value.

## Chapter 4

# EXAMPLE

See `ubftest/test_expr.c` for sample code.

## Chapter 5

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)



## Chapter 6

## SEE ALSO

**CBchg(3) Badd(3) Binit(3) Bstrerror(3) Berror(3)**

# Chapter 7

# COPYING

© Mavimax, Ltd