

NDRX_ATFORK_CHILD(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | BUGS | 5 |
| 6 | SEE ALSO | 6 |
| 7 | COPYING | 7 |

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
void ndrx_atfork_child(void);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

When process is copied by **fork()** system call, **ndrx_atfork_child()** shall be executed by child process after the fork call. This ensures that Enduro/X sub-systems for child process cleans up any open resources. Particularly fork is done by XATMI server then function deallocates any server resources open. **NOTE** that if any thread is doing XATMI client tasks, then **tpterm(3)** shall be called period fork is done.

The logic of function is subject of change and in future releases some other tasks might be required to be done by Enduro/X after process forking, thus it is recommended to use **ndrx_fork()**, call manually **ndrx_atfork_chikld()** or register it with **pthread_atfork()**

Chapter 3

RETURN VALUE

N/A

Chapter 4

ERRORS

N/A

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

`ndrx_fork(3)` `ndrx_atfork_prepare(3)` `ndrx_atfork_parent(3)`

Chapter 7

COPYING

© Mavimax, Ltd