

EX_ENVOVER(5)

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	PARAMTERS	3
4	EXAMPLE	4
5	BUGS	5
6	SEE ALSO	6
7	COPYING	7

Chapter 1

SYNOPSIS

Configuration file syntax:

```
# this line is commented
export PARAM_NAME=VALUE
#
PARAM_NAME_2=PARAM_VALUE_2
```

Chapter 2

DESCRIPTION

This is simple text file with shell like syntax for environment variable setup. Used for per ATMI server environment process environment variable override. File is configured in **ndrxconfig.xml(5)** config file.

Chapter 3

PARAMTERS

PARAM_NAME

Name of the of the environment variable to be overridden.

VALUE

The value to be used. The value starting from = is directly loaded into memory. All symbols up till end of the line are used.

Chapter 4

EXAMPLE

Sample configuration:

```
#
# This is environment override file for tpevsrv
#

# Syntax is following:
# # = comment
# [export ] = ignored
# ENV_VAR = name of env
# = = equals sign
# VALUE

# Just for test, we set not clusterized
export NDRX_CLUSTERISED=0

# Also for testing se set wrong node id.
NDRX_NODEID=9
```

Chapter 5

BUGS

Report bugs to © Mavimax, Ltd

Chapter 6

SEE ALSO

[xadmin\(8\)](#), [ndrxd\(8\)](#), [ndrxconfig.xml\(5\)](#), [ndrxdebug.conf\(5\)](#), [ndrxconfig.xml\(5\)](#)

Chapter 7

COPYING

© Mavimax, Ltd
