VIEWFILE(5)

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

Chapter 1

SYNOPSIS

Formal specification:

```
# First view in the file
VIEW VIEWNAME

FLD_TYPE      C_NAME      UBF_NAME    COUNT      FLAGS      SIZE       NULL_VAL
...
FLD_TYPE_N    C_NAME_N    UBF_NAME_N COUNT_N    FLAGS_N    SIZE_N     NULL_VAL_N

END

...

# N view in the view file
VIEW VIEWNAME_N

...

END
```

Example view: (test.v):

```
VIEW MYVIEW1
#type     cname       fbname              count   flag    size    null

short     tshort1     T_SHORT_FLD         1       FS      -       2000
short     tshort2     T_SHORT_2_FLD       2       FSC     -       2001
short     tshort3     T_SHORT_3_FLD       3       FSC     -       -
short     tshort4     -                   1       N       -       NONE

long      tlong1      T_LONG_FLD          1       FS      -       0
int       tint2       T_LONG_2_FLD        2       FS      -        0
int       tint3       -                   1       -       -       -1
int       tint4       -                   2       -       -       -1

char      tchar1      T_CHAR_FLD          1       F       -       '\n'
char      tchar2      T_CHAR_2_FLD        5       SC      -       'A'
char      tchar3      T_CHAR_3_FLD        2       CN      -       -

float     tfloat1     T_FLOAT_FLD         4       FS      -       1.1
float     tfloat2     T_FLOAT_2_FLD       2       S       -       -
float     tfloat3     -                   1       N       -       9999.99

double    tdouble1    T_DOUBLE_FLD        2       FS      -       55555.99
```

```
double   tdouble2   T_DOUBLE_2_FLD      1        F        -        -999.123

string   tstring0   -                  3        -        18       '\n\t\f\\\'\"\vHELLOWORLD'
string   tstring1   T_STRING_FLD       3        FSP      20       'HELLO WORLDB'
string   tstring2   T_STRING_2_FLD     3        FCL      20       -
string   tstring3   T_STRING_3_FLD     4        FSCL     20       'TESTEST'
string   tstring4   -                  1        P        15       'HELLO TEST'
string   tstring5   -                  1        -        15       'MEGA TEST'

carray   tcarray1   T_CARRAY_FLD       1        FS       30       '\0\n\t\f\\\'\"\vHELLOWORLD ←
    '
carray   tcarray2   T_CARRAY_2_FLD     1        LFSP     25       '\0\n\t\f\\\'\"\vHELLOWORL\ ←
    n'
carray   tcarray3   T_CARRAY_3_FLD     10       FSCLP    30       '\0\\\nABC\t\f\'\vHELLO'
carray   tcarray4   -                  1        -        5        'ABC'
carray   tcarray5   -                  1        -        5        -

END
```

Compiled header output (C language mode):

```
struct MYVIEW1 {
        short   tshort1;        /* null=2000 */
        short   C_tshort2;
        short   tshort2[2];     /* null=2001 */
        short   C_tshort3;
        short   tshort3[3];
        short   tshort4;        /* null=NONE */
        long    tlong1; /* null=0 */
        int     tint2[2];       /* null=0 */
        int     tint3;  /* null=-1 */
        int     tint4[2];       /* null=-1 */
        char    tchar1; /* null="\n" */
        short   C_tchar2;
        char    tchar2[5];      /* null="A" */
        short   C_tchar3;
        char    tchar3[2];
        float   tfloat1[4];     /* null=1.1 */
        float   tfloat2[2];
        float   tfloat3;        /* null=9999.99 */
        double  tdouble1[2];    /* null=55555.99 */
        double  tdouble2;       /* null=-999.123 */
        char    tstring0[3][18];        /* null="\n\t\f\\\'\"\vHELLOWORLD" */
        char    tstring1[3][20];        /* null="HELLO WORLDB" */
        short   C_tstring2;
        unsigned short  L_tstring2[3];
        char    tstring2[3][20];
        short   C_tstring3;
        unsigned short  L_tstring3[4];
        char    tstring3[4][20];        /* null="TESTEST" */
        char    tstring4[15];   /* null="HELLO TEST" */
        char    tstring5[15];   /* null="MEGA TEST" */
        char    tcarray1[30];   /* null="\0\n\t\f\\\'\"\vHELLOWORLD" */
        unsigned short  L_tcarray2;
        char    tcarray2[25];   /* null="\0\n\t\f\\\'\"\vHELLOWORL\n" */
        short   C_tcarray3;
        unsigned short  L_tcarray3[10];
        char    tcarray3[10][30];       /* null="\0\\\nABC\t\f\'\vHELLO" */
        char    tcarray4[5];    /* null="ABC" */
        char    tcarray5[5];
};
```

Chapter 2

DESCRIPTION

View files (usually with extension *.v*) describe the data block or structure which later is generated by *viewc(8)* binary. The view compiler generate C header file for view file. Also the compiler generate the *object-file* with extension *.V*. The object-file basically is the same view file except it contains platform specific meta data. For each platfrom (OS/CPU changes), view file shall be re-compiled. How ever during the middleware operations, the message view message produced on one platform is transferable on the other platform. This basically is the core view feature, so that programmer may operate with C structures, but the middleware ensures that structure is successfully delivered to the target system in cross platform way.

View files may describe single element or array of the element (e.g. *tshort1*). The arrays are supported for STRING and CARRAY fields too. In those cases those are two dimensional arrays.

For STRING and CARRAY types, length can be specified. The length is given in total number of bytes. So if you want to store "ABC", you will need to specify *count* 4, one extra byte for EOS (zero terminator).

The next section describes each of the view file elements.

FLD_TYPE C_NAME FB_NAME COUNT FLAGS SIZE NULL_VAL

Chapter 3

VIEW FILE ELEMENTS

FLD_TYPE

Field type. This is how the field will be presented in the C structure. Following types are supported: **short**, **long**, **char**, **float**, **double**, **string** and **carray**. Carray is a blob, which might contain binary zero byte (0x00).

C_NAME

Field name in c structure. The rule against the field name applies the standard ones which applies to C variable names. **viewc** accepts max length of the 256 for the C identifier. But actual size is determined by compiler.

UBF_NAME

Optional UBF buffer field name. This is used by **Bvstof(3)** - convert C struct to UBF buffer. And by **Bvftos(3)** - convert UBF buffer to c structure. If the setup of the UBF field is not needed, then field can be skipped with "-" (minus sign in view file). In that case no mappings are processed. During the **Bvstof** and **Bvftos** invocation. If field is set, then **FLAGS** field changes the logic how the mapping is processed.

COUNT

This array element count. As in view file each of the c fields can be array, this defines the behavior. If field is set to **1**, then field is created as a normal one. If count > 1, then array is defined. The count cannot be less than 1, in such case view compiler will give an error. For **CARRAY** and **string** fields, count greater that 1 will create basically two dimensional array, where one dimension is count and another dimension is size.

FLAGS

There are defined several flags for the view file. For values see the section bellow. If not flags are set, then value "-" shall be used in view descriptor. Some options of the flags can be changed in the runtime with **Bvopt(3)** function.

SIZE

Number of bytes for **string** or **carray** definition. For other field types it is not valid to be set and will cause **viewc** complication error. For **string** and **carray** it is mandatory to be set size set. For other types use value "-".

NULL_VAL

This is NULL value for the field. The NULL value indicates the value when it can be considered that field is empty. The NULL value is used for following cases: 1) When transferring data from C to UBF buffer by **Bvstof(3)**. Each field is tested against NULL value. If field is NULL and the updated mode **BUPDATE**, then field is not copied to target buffer. In case of multiple occurrences, the occurrence will be lost if next C array element is not NULL. To use default NULL specification, use "-" field. Which means 0 for short/long/int. 0.0f for float/double, "" - for string and zero length carray. To encode special symbols, spaces in the NULL value, use single or double quoted string. The view compiler recognizes following escape sequences \0 - for 0x00 byte, \n, \t , \f, \\, "'", \", \v. For string NULLs the EOS terminator 0x00 byte is not needed. NULL values are used during the **tpcalloc(3)** operation. The buffer is initialized with default values by help of the **Bvsinit(3)** function. To set individual field to the NULL value use **Bvselinit(3)**. To test the field for NULL value use **Bvnull(3)**. If no NULL value is present for a field use keyworkd NONE wiht out quotes. In that case no value will be considered NULL. This will mean that any value will be transfered to UBF. And any value will be copied over to desination service when doing **tpcall(3)**.

Chapter 4

VIEW FLAGS

F

Map the field from C struct to UBF (will be processed by **Bvstof(3)**).

S

Map the field from UBF to C struct (will be processed by **Bvftos(3)**).

N

Do not perform UBF mappings at all (**Bvstof(3)**, **Bvftos(3)** will skip the field in the same way as "-" value used for flags.).

C

Flag means generate count indicator for the field. The count field type is *short*. The count field is made as *C_* prefix for the C field name. If other field is named as combination of *C_* and this field name, then C compiler will generate error as duplicate member of the structure. The count field participates during the data transfer to UBF buffer via **Bvstof(3)**, **Bvftos(3)** commands. For the transfer for to the UBF, the count will indicate occurrences to transfer. For example 0, will make zero transfer (buffer will not be setup). The count field participates also in structure transfer view **tpcall(3)** or other buffer related IPC operation. The actual data transfered to the target system will depend on count field. The other elements in target system will be initialized with NULL value, defined in view. If count field is not set (no **C** flag present), all occurrences will be sent to the target system. And all occurrences will be copied to the UBF buffer. When data is transfered from UBF to C structure, then count field is set to number occurrences are written in the structure. For sample reference, see *C_tshort2* field and its original *tshort2* definition.

L

If this flag is set, then additional length indicator(s) are generated. This is used to indicate the actual length for the **CARRAY** data, to be written to UBF buffer. If data is converted fro UBF buffer to C structure, then field will indicate the number of bytes copied to C structure. In case of strings, the field is updated only in case when data is copied from UBF to C struct, in that case it is set to number of bytes written to C struct. When converting from C to UBF, for strings this length value is ignored and EOS termination of the string are used for length indication. The length field is produced as prefix *L_* for the given field. In the same way as for **C**, there might be conflict with duplicate field if another field is already as this field prefixed with *L_*. The field type is *unsigned short*. IF **COUNT** is greater than 1, then length indicators are array of *unsigned short*, because the length indication must be processed for each of the elements in array. If **L** flag is not set, then for **carray** full buffer size is copied to UBF and back. The length plays similar role for C struct data transfer over the **tpcall(3)** and other IPC operations. Only the number set it length are transfered to target service for the **CARRAY** fields.

Chapter 5

EXAMPLE

See **atmitest/test040_typedview** for sample usage.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

viewc(8), **Bvftos(3)**, **Bvstof(3)**, **Bvsinit(3)**, **Bvselinit(3)**, **Bvnull(3)**, **Bvopt(3)**, **Bvrefresh(3)**

Chapter 8

COPYING

© Mavimax, Ltd