

**BSTRError(3)**

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>ERRORS</b>	<b>4</b>
<b>5</b>	<b>BUGS</b>	<b>5</b>
<b>6</b>	<b>SEE ALSO</b>	<b>6</b>
<b>7</b>	<b>COPYING</b>	<b>7</b>

---

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * Bsterror (int err);
```

```
Link with -lubf -lnstd -lm -lpthread
```

## Chapter 2

# DESCRIPTION

Function returns string description of given error code. Enduro/X also logs additional information for last error state, and that information is returned in string format together with description of *err*. Typically when error occurs, then programmer calls **Bsterror(Berror)**, thus function will closely describe what was happened. However if programmer calls **Bsterror()** with other error code, then message will contain the description of *err* plus last UBF call's logged error info. Then message and **Berror** infos are stored in thread local storage (TLS).

---

## Chapter 3

# RETURN VALUE

String containing formatted error code description plus last call's error logged info. For example:

```
...
/* call the service now! */
char username[100];
BFLDLEN len=sizeof(username);
if (SUCCEED!=Bget(p_ub, USER_NAME, 0, buf, &len))
{
    ret=FAIL;
    /* print the result */
    fprintf(stderr, "%s\n", Bsterror(Berror));
}
...
```

## Chapter 4

# ERRORS

Function does not return any errors.

---

## Chapter 5

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

---

## Chapter 6

# SEE ALSO

**Berror(3)** **B\_error(3)**

## **Chapter 7**

# **COPYING**

© Mavimax, Ltd

---