

BDEL(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
int Bdel (UBFH * p_ub, BFLDID bfldid, BFLDOCC occ);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Delete the field *bfl**did* with occurrence *occ* from UBF buffer *p_ub*.

Chapter 3

RETURN VALUE

On success, **Bdel()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted.

BBADFLD Invalid field id passed.

BNOTPRES Field not present.

Chapter 5

EXAMPLE

See `ubftest/test_bdel.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bchg(3) Badd(3) CBadd(3) Bget(3) Badd(3)

Chapter 8

COPYING

© Mavimax, Ltd