

**TPGETLEV(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1 SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2 DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3 RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4 ERRORS</a>	<a href="#">4</a>
<a href="#">5 EXAMPLE</a>	<a href="#">5</a>
<a href="#">6 BUGS</a>	<a href="#">6</a>
<a href="#">7 SEE ALSO</a>	<a href="#">7</a>
<a href="#">8 COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <atmi.h>
```

```
int tpgetlev (void);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

---

## Chapter 2

# DESCRIPTION

Function returns current status of global transaction. If transaction is started by **tpbegin()** or called service is part of global transaction (invoked by process in global TX and was not specified **TPNOTRAN**), then function returns *1*. If process is not part of global transaction, then return value is **0**.

---

## Chapter 3

# RETURN VALUE

**0** - current thread is not part of global transaction. **1** - current thread is part of global transaction.

## Chapter 4

# ERRORS

Function does not return any errors.

## Chapter 5

# EXAMPLE

See `atmitest/test021_xafull/atmisv21.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

`tpcommit(3)` `tgetlev(3)` `tpopen(3)` `tpsuspend(3)` `tpresume(3)`

## Chapter 8

# COPYING

© Mavimax, Ltd