

BCMP(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | ERRORS | 4 |
| 5 | EXAMPLE | 5 |
| 6 | BUGS | 6 |
| 7 | SEE ALSO | 7 |
| 8 | COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
int Bcmp (UBFH *p_ubf1, UBFH *p_ubf2);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Compares two UBF buffers.

Chapter 3

RETURN VALUE

If buffer are equal, value **0** is returned. If *p_ubf1* have lesser fields, field id is lesser than *p_ubf2* or value of field is lesser than *p_ubf2* then **-1** is returned. In the same way if *p_ubf1* is greater *p_ubf2*, then value **1** is returned.

Chapter 4

ERRORS

In case of error **Berror** will be non **0**. Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BEINVAL *p_ubf1* or *p_ubf2* are NULL pointers.

BNOTFLD *p_ubf1* or *p_ubf2* buffers not fielded, not correctly allocated or corrupted.

Chapter 5

EXAMPLE

See `ubftest/test_bcmp.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bsubset(3)

Chapter 8

COPYING

© Mavimax, Ltd