

# EXENCRYPT(8)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>EXAMPLE</b>	<b>3</b>
<b>4</b>	<b>EXIT STATUS</b>	<b>4</b>
<b>5</b>	<b>BUGS</b>	<b>5</b>
<b>6</b>	<b>SEE ALSO</b>	<b>6</b>
<b>7</b>	<b>COPYING</b>	<b>7</b>

## Chapter 1

# SYNOPSIS

**exencrypt** STRING [STRING...]

## Chapter 2

# DESCRIPTION

Program encrypts the **STRING** value passed on command line. In the result program prints to **stdout** encrypted value of the string. The encrypted values is base64 string. The debug is configured in standard way as for all other binaries via *ndrxdebug.conf* or Common Config.

Encryption keys which are used for encryption are provided either by using built-in algorithm (username+hostname) hashed with SHA1. Or from vendor specific loaded plugin.

The encryption principles allows to encrypt the sensitive data and store on disk in PCI/DSS compatible way.

---

## Chapter 3

# EXAMPLE

Single string encryption:

```
$ exencrypt 'HELLO WORLD'
AAAAC196L/d4Sj4OC8cSZh2492I=
```

Two string encryption:

```
$ exencrypt HELLO WORLD
AAAABbBtKbtIv9BXelSioTYi5xw=
AAAABRaPhXxibr6ZktcZ6S71i50=
```

## Chapter 4

# EXIT STATUS

**0**      Success

**1**      Failure

## Chapter 5

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 6

## SEE ALSO

`exdecrypt(8)`, `ex_env(5)`, `ndrxdebug.conf(5)`

## Chapter 7

# COPYING

© Mavimax, ltd.