

**Boccur(3)**

| REVISION HISTORY |      |             |      |
|------------------|------|-------------|------|
| NUMBER           | DATE | DESCRIPTION | NAME |
|                  |      |             |      |

# Contents

|          |                     |          |
|----------|---------------------|----------|
| <b>1</b> | <b>SYNOPSIS</b>     | <b>1</b> |
| <b>2</b> | <b>DESCRIPTION</b>  | <b>2</b> |
| <b>3</b> | <b>RETURN VALUE</b> | <b>3</b> |
| <b>4</b> | <b>ERRORS</b>       | <b>4</b> |
| <b>5</b> | <b>EXAMPLE</b>      | <b>5</b> |
| <b>6</b> | <b>BUGS</b>         | <b>6</b> |
| <b>7</b> | <b>SEE ALSO</b>     | <b>7</b> |
| <b>8</b> | <b>COPYING</b>      | <b>8</b> |

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
BFLDOCC Boccur (UBFH *p_ub, BFLDID bfldid);
```

```
Link with -lubf -lnstd -lm -lpthread
```

## Chapter 2

# DESCRIPTION

Get the number of field occurrences in buffer. *p\_ub* is pointer to **UBF** buffer (allocated with `tpalloc(3)`, buffer type "UBF", "FML" or "FML32"). *bflid* is UBF buffer field id (which is generated by `mkfldhdr(8)`).

---

## Chapter 3

# RETURN VALUE

On success, **Boccur()** returns number of field occurrences; If field not found, then return is **0**; on error, **-1** is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Bsterror(3) can give more description for error (for last call).

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted. p\_ub is NULL.

**FBADFLD** Invalid field type.

---

## Chapter 5

# EXAMPLE

See `ubftest/ubfunit1.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

# Chapter 7

# SEE ALSO

**Badd(3)** **Bfind(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd