

**BTYPCVT(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1</a>	<a href="#">SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3</a>	<a href="#">RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4</a>	<a href="#">ERRORS</a>	<a href="#">4</a>
<a href="#">5</a>	<a href="#">EXAMPLE</a>	<a href="#">5</a>
<a href="#">6</a>	<a href="#">BUGS</a>	<a href="#">6</a>
<a href="#">7</a>	<a href="#">SEE ALSO</a>	<a href="#">7</a>
<a href="#">8</a>	<a href="#">COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * Btypcvt (BFLDLEN *to_len, int to_type, char *from_buf, int from_type, BFLDLEN from_len);
```

```
Link with -lubf -lnstd -lm -lpthread
```

---

## Chapter 2

# DESCRIPTION

Convert the data from *from\_buf/from\_type/from\_len* triplet to type in *to\_type*. The length is returned in *to\_len*. Length is mandatory for **BFLD\_CARRAY** types, for others they can be NULL. Function returns the pointer to data block, which is malloced by this function.

The memory allocated by this function user shall free with standard **free()** system call.

---

## Chapter 3

# RETURN VALUE

On success, **Btypcvt()** return pointer to allocated memory with converted data; on error, NULL is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BTYPERR** Invalid from/to type specified.

**BEINVAL** *from\_buf* is NULL.

**BMALLOC** Failed to allocate type conversion buffer.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_genbuf.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**CBget(3)** **CBchg(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd