

# **TPSRVFREECTXDATA(3)**

**REVISION HISTORY**

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1 SYNOPSIS</b>	<b>1</b>
<b>2 DESCRIPTION</b>	<b>2</b>
<b>3 RETURN VALUE</b>	<b>3</b>
<b>4 ERRORS</b>	<b>4</b>
<b>5 EXAMPLE</b>	<b>5</b>
<b>6 BUGS</b>	<b>6</b>
<b>7 SEE ALSO</b>	<b>7</b>
<b>8 COPYING</b>	<b>8</b>

# Chapter 1

## SYNOPSIS

```
#include <atmi.h>
void tpsrvfreetxdata(char *p_buf);
Link with -latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm
```

## Chapter 2

### DESCRIPTION

Function is used for deallocating the server context data allocated either by **tpsrvgetctxdata(3)** or **tpsrvgetctxdata2()**.

This function is available only for XATMI servers.

## Chapter 3

# RETURN VALUE

Function does not return a value.

## Chapter 4

# ERRORS

Function does not return an error.

## Chapter 5

### EXAMPLE

See **atmitest/test017\_srvthread/atmisv17.c** for sample code.

## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

---

## Chapter 7

### SEE ALSO

**tpsetctxdata(3) tpsrvgetctxdata(3) tpcontinue(3) tpinit(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd