

BSIZEOF(3)

REVISION HISTORY

| NUMBER | DATE | DESCRIPTION | NAME |
|--------|------|-------------|------|
| | | | |

Contents

| | |
|-----------------------|----------|
| 1 SYNOPSIS | 1 |
| 2 DESCRIPTION | 2 |
| 3 RETURN VALUE | 3 |
| 4 ERRORS | 4 |
| 5 EXAMPLE | 5 |
| 6 BUGS | 6 |
| 7 SEE ALSO | 7 |
| 8 COPYING | 8 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
long Bsizeof (UBFH *p_ub);
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Return the UBF buffer size in bytes.

Chapter 3

RETURN VALUE

On success, **Bsizeof()** return buffer size; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Bstrerror(3) can give more description for error (for last call).

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted. p_ub is NULL.

Chapter 5

EXAMPLE

See **ubftest/ubfunit1.c** for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Binit(3) Bused(3) Bunused(3)

Chapter 8

COPYING

© Mavimax, Ltd