

# BBOOLSETCBF(3)

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>ERRORS</b>	<b>4</b>
<b>5</b>	<b>EXAMPLE</b>	<b>5</b>
<b>6</b>	<b>BUGS</b>	<b>6</b>
<b>7</b>	<b>SEE ALSO</b>	<b>7</b>
<b>8</b>	<b>COPYING</b>	<b>8</b>

---

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
int Bboolsetcbf (char funcname, long (functionPtr)(UBFH *p_ub, char *funcname));
```

Link with *-lubf -lnstd -lm -lpthread*

---

## Chapter 2

# DESCRIPTION

Register callback function to boolean expression evaluator. The function name which appears in UBF expression is set in *funcname*, the function it self is set passed in *functionPtr*. The callback function receives the buffer on which it is being evaluated in *p\_ub*, and callback receives the function name too in *funcname*.

Min length for function name is 3 symbols and max length is 64.

---

## Chapter 3

# RETURN VALUE

On success, **Bboolsetcbf()** returns **0**. On error **-1** is returned, with **Berror** set to indicate the error.

---

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BBADNAME** Invalid function name

---

## Chapter 5

# EXAMPLE

See `ubftest/test_expr.c` for sample code.

---

## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

---

## Chapter 7

## SEE ALSO

**Bboolco(3)** **Bfloatev(3)** **Btreefree(3)**

---

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd

---