

Bnum(3)

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1 SYNOPSIS	1
2 DESCRIPTION	2
3 RETURN VALUE	3
4 ERRORS	4
5 EXAMPLE	5
6 BUGS	6
7 SEE ALSO	7
8 COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
BFLDOCC Bnum (UBFH *p_ub);
Link with -lubf -lnstd -lm -lpthread
```

Chapter 2

DESCRIPTION

Get the number of all field occurrences in buffer. *p_ub* is pointer to **UBF** buffer (allocated with tpalloc(3), buffer type "UBF", "FML" or "FML32").

Chapter 3

RETURN VALUE

On success, **Bnum()** returns number of all field occurrences; If fields not found, then return is **0**; on error, **-1** is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Bstrerror(3) can give more description for error (for last call).

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted. p_ub is NULL.

FBADFLD Invalid field type.

Chapter 5

EXAMPLE

See **ubftest/test_bnum.c** for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Boccur(3) Bpres(3)

Chapter 8

COPYING

© Mavimax, Ltd