

BSIZEOF(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1 SYNOPSIS	1
2 DESCRIPTION	2
3 RETURN VALUE	3
4 ERRORS	4
5 EXAMPLE	5
6 BUGS	6
7 SEE ALSO	7
8 COPYING	8

Chapter 1

SYNOPSIS

`#include <ubf.h>`

`long Bsizeof (UBFH *p_ub);`

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Return the UBF buffer size in bytes.

Chapter 3

RETURN VALUE

On success, **Bsizeof()** return buffer size; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Bsterror(3) can give more description for error (for last call).

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted. p_ub is NULL.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Binit(3) Bused(3) Bunused(3)

Chapter 8

COPYING

© ATR Baltic, SIA