

TPUNADVERTISE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
int tpunadvertise(char *svcname);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Remove service in parameter *svcname* from Enduro/X application server service registry. Service previously must be advertised by server process by **tpadvertise()** or by service aliasing which was done during process startup with configuration in **ndrxconfig.xml(5)**.

This function is available only for XATMI servers.

Chapter 3

RETURN VALUE

On success, **tpunadvertise()** return zero; on error, -1 is returned, with **tperrno** set to indicate the error.

Chapter 4

ERRORS

Note that **tpsterror()** for returns generic error message plus custom message with debug info from last call.

TPENOENT Service not advertised by current XATMI server process.

TPEOS Operating system error, that could insufficient memory or other error or problem with manipulating with underlaying queues. The Enduro/X logs (**ndrxdebug.conf**) for more infos.

TPESYSTEM Failed to updated **ndrxd** for changes in service registry.

Chapter 5

EXAMPLE

See `atmitest/test007_advertise/atmisv.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

tpadvertise(3) ndrxd(8) ndrxddebug.conf(5) ndrxdconfig.xml(5)

Chapter 8

COPYING

© ATR Baltic, SIA