

BFREE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
int Bfree (UBFH *p_ub);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Free up the buffer allocated by Balloc(3). After the function call *p_ub* pointer becomes invalid.

Chapter 3

RETURN VALUE

On success, **Bfree()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

Chapter 4

ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BALIGNERR Corrupted buffer or pointing to not aligned memory area.

BNOTFLD Buffer not fielded, not correctly allocated or corrupted.

Chapter 5

EXAMPLE

See `ubftest/test_mem.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

Balloc(3) Brealloc(3) Binit(3)

Chapter 8

COPYING

© ATR Baltic, SIA