

**CBGETALLOC(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * CBgetalloc (UBFH *p_ub, BFLDID bfldid, BFLDOCC occ, int usrtype, BFLDLEN *extralen);
```

```
Link with -lubf -lnstd -lm -lpthread
```

---

## Chapter 2

# DESCRIPTION

Get the field *bfl**did* at *occ* occurrence from *p\_ub* buffer. The value is converted to *usrtype*. The value is returned (copied to) to memory block allocated by function. There is extra parameter *extralen*. On input it indicates the additional space that shall be allocated. The *extralen* can be NULL, in that case no extra memory is allocated.

Function is based on **Bgetalloc(3)**, which does not convert to user type, but returns direct value.

## Chapter 3

# RETURN VALUE

On success, **CBgetalloc()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

**BNOTPRES** Field not present.

**BMALLOC** Failed to allocate type conversion buffer.

**BBADFLD** Invalid field passed to *bfldid*.

**BTYPERR** Invalid user type specified.

## Chapter 5

# EXAMPLE

See `ubftest/test_get.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bchg(3) Badd(3) CBadd(3) Bfind(3) Bgetalloc(3)**

## Chapter 8

# COPYING

© Mavimax, Ltd