

**REALLOC(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1</a>	<a href="#">SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3</a>	<a href="#">RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4</a>	<a href="#">ERRORS</a>	<a href="#">4</a>
<a href="#">5</a>	<a href="#">EXAMPLE</a>	<a href="#">5</a>
<a href="#">6</a>	<a href="#">BUGS</a>	<a href="#">6</a>
<a href="#">7</a>	<a href="#">SEE ALSO</a>	<a href="#">7</a>
<a href="#">8</a>	<a href="#">COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
UBFH * Brealloc (UBFH *p_ub, BFLDOCC f, BFLDLEN v);
```

Link with *-lubf -lnstd -lm -lpthread*

---

## Chapter 2

# DESCRIPTION

Reallocates UBF buffer to store the number of fields of  $f$  with total data length of  $v$  bytes, length must include zero terminator byte for strings.

## Chapter 3

# RETURN VALUE

On success, **Brealloc()** returns pointer to UBF buffer; on error, NULL is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BEINVAL** Buffer is shorter than currently bytes used, or the total size of bigger than **MAXUBFLEN**.

**BMALLOC** Malloc failed.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_mem.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bfree(3)** **Balloc(3)** **Binit(3)** **Bused(3)** **Bneeded(3)**

## Chapter 8

# COPYING

© Mavimax, Ltd