

**BFLOATEV(3)**

| REVISION HISTORY |      |             |      |
|------------------|------|-------------|------|
| NUMBER           | DATE | DESCRIPTION | NAME |
|                  |      |             |      |

# Contents

|          |                     |          |
|----------|---------------------|----------|
| <b>1</b> | <b>SYNOPSIS</b>     | <b>1</b> |
| <b>2</b> | <b>DESCRIPTION</b>  | <b>2</b> |
| <b>3</b> | <b>RETURN VALUE</b> | <b>3</b> |
| <b>4</b> | <b>ERRORS</b>       | <b>4</b> |
| <b>5</b> | <b>EXAMPLE</b>      | <b>5</b> |
| <b>6</b> | <b>BUGS</b>         | <b>6</b> |
| <b>7</b> | <b>SEE ALSO</b>     | <b>7</b> |
| <b>8</b> | <b>COPYING</b>      | <b>8</b> |

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
double Bfloatev (UBFH *p_ub, char *tree);
```

```
Link with -lubf -lnstd -lm -lpthread
```

## Chapter 2

# DESCRIPTION

Evaluate compiled expression in *tree* against UBF buffer in *p\_ub*. Returned value is floating point result of the operation.

## Chapter 3

# RETURN VALUE

Floating point result value is returned. In case of error it is **-1**, but to detect error, check the **Berror**.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BNOTFLD** *p\_ub* is not fielded buffer or argument NULL.

**BEINVAL** *tree* param is NULL.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

**BBADFLD** Invalid field id passed.

**BNOTPRES** Field not present.

**FMALLOC** Malloc failed.

**BSYNTAX** Synax error in script.

**BBADNAME** Bad field name specified.

## Chapter 5

# EXAMPLE

See `ubftest/test_expr.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bboolco(3)** **Bboolev(3)** **Btreefree(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd