

TPLOGCLOSEREQFILE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ndebug.h>
```

```
void tplogclosereqfile(void);
```

Link with *-lstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Close currently open request logging facility. It is not a problem to call a function twice. If request logger is closed nothing will happen. With this function logger will be degraded to thread logging facility (if was open) or to process based logging.

Function applies to all Enduro/X logging facilities: **TP**, **NDRX** and **UBF**, thus when request logging is closed, any facility is degraded thread or process logging.

Chapter 3

RETURN VALUE

N/A

Chapter 4

ERRORS

N/A

Chapter 5

EXAMPLE

See `atmitest/test031_logging/atmict31.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

`tplogclosethread(3)` `tplogsetreqfile_direct(3)` `tplogsetreqfile(3)` `tplogdump(3)` `tplogdumpdiff(3)` `tplog(3)` `tplogconfig(3)` `ex_devguid`

Chapter 8

COPYING

© Mavimax, Ltd